

## Main technical indicators(主要技术指标)

|                                 |                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                 | 5000                                                                                                                 |
| 2.Working Temperature (温度)      | -55~+150 ℃                                                                                                           |
| 3.IP Rating (防护级别)              | IP 54                                                                                                                |
| 4.Diameter of socket end(插合端直径) | φ2.0                                                                                                                 |
| 5.Testing Voltage (测试电压)        | 1900V                                                                                                                |
| 6.Working Voltage (工作电压)        | 1500V                                                                                                                |
| 7.Rated Current (额定电流)          | 25A                                                                                                                  |
| 8.Shell material(壳体材质)          | Brass (chromium plating) shell and chuck nut/( nickel plating) pin sleeve and middleware/黄铜 (镀铬) 外壳和夹头螺母/(镀镍)插销套和中间件 |
| 9.Pin Material(插针材料)            | Copper alloy gold plating(铜合金镀金)                                                                                     |
| 10.Insulator material(绝缘体材质)    | PPS                                                                                                                  |


## Sum up(总结)

|                             |                                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Series(系列)                  | B                                                                                                                                 |
| Shell style/model (外壳样式/型号) | TEG: Straight plug, cable collet, front seal and nut for fitting a bend relief (IP 54 when mated) 直塞、电缆夹头、前密封件和用于安装弯曲凸起 (配对时IP54) |
| Button (按键)                 | A button(一个按键)                                                                                                                    |
| Termination type (终止类型)     | Male solder(公焊锡)                                                                                                                  |
| Line diameter awg(线材直径)     | 22-14AWG                                                                                                                          |
| Cable diameterφ (电缆直径)      | φ10.1-11MM                                                                                                                        |
| Matching parts(配件)          | ZGG.3B.P03.CLL                                                                                                                    |



## Location pin combination(定位销组合)

| (编号)<br>Number | Number of<br>positioning pins(定<br>位销数量) | Angle(<br>角度) | Series(系列)-3B           |
|----------------|------------------------------------------|---------------|-------------------------|
| G              | One(1)                                   |               | (Zero degrees)0°        |
| A              | Two(2)                                   | A             | Thirty degrees(30°)     |
| B              | Two(2)                                   |               | Forty-five degrees(45°) |
| C              | Two(2)                                   |               | Sixty degrees(60°)      |
| D              | Two(2)                                   | Y             | 95 degrees (95°)        |
| E              | Two(2)                                   | β             | 120 degrees(120°)       |
| F              | Two(2)                                   |               | 145 degrees(145°)       |
| J              | Two(2)                                   | A             | 37.5degrees(37.5°)      |
| K              | Two(2)                                   |               | 52.5degrees(52.5°)      |
| L              | Two(2)                                   | Y             | Seventy degrees(70°)    |

|        | A      | B      | C      | ANGLE   |      |
|--------|--------|--------|--------|---------|------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1 |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5 |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |      |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |      |



|    | A     | L      | M      | S1     | S2     |
|----|-------|--------|--------|--------|--------|
| MM | φ19   | 56.5   | 41.5   | 15.0   | 15     |
| in | 0.748 | 2.2244 | 1.6339 | 0.5906 | 0.5906 |

Welded surface  
(焊接面)Positive view  
(正视图)Solder core  
(焊接型公胶芯)

TE G. 3B. P03.C L A D 11 H

Model(型号)

Positioning pin(定位销)

Series(系列)

Needle core configuration(针芯配置)

Outer casing(外壳)

Insulator(绝缘体)

Needle core(针芯)

Type of clamp(线夹类型)

Cable diameter(电缆直径)

SH means a sheath type, not a cover type.  
(H表示护套型, 不表示为不带护套型)

|                                |          |                                      |          |                                         |
|--------------------------------|----------|--------------------------------------|----------|-----------------------------------------|
| DESIGNED(设计)                   | DATE(日期) | SCALE(比例)                            | N/A(不适用) | MODEL TYPE<br>型号类型: TEG.3B.P03.CLAD.11H |
| CHECKED(校对)                    | DATE(日期) | VIEW(视图)                             |          | PART NO. 3B3-core plug<br>名称: 3B3芯插头    |
| APPROVED(审核)                   | DATE(日期) | UNIT(单位)                             | MM       | DWG NO.:                                |
| REVISIONS                      |          | MATERIAL (材料)                        |          | WEIGHT(重量) SHEET(张) REVISION(修订)        |
| www.helloxb.com www.helloxb.cn |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | 1/1 A0                                  |