


## 1.View and size(视图及尺寸)

| Main technical indicators(主要技术指标) |                                                                               |
|-----------------------------------|-------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                          |
| 2.Working Temperature (温度)        | -55~+150 ℃                                                                    |
| 3.IP Rating (防护级别)                | IP 50                                                                         |
| 4.Diameter of socket end(插合端直径)   | Ø1.3                                                                          |
| 5.Testing Voltage (测试电压)          | 1750V                                                                         |
| 6.Working Voltage (工作电压)          | 1600V                                                                         |
| 7.Rated Current (额定电流)            | 14A                                                                           |
| 8.Shell material(壳体材质)            | Brass (chromium plating)/(nickel plating) fixation ring/<br>黄铜 (镀铬) /(镀镍) 固定圈 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                              |
| 10.Insulator material(绝缘体材质)      | PPS                                                                           |


| Sum up(总结)                  |                                                       |
|-----------------------------|-------------------------------------------------------|
| Series(系列)                  | B                                                     |
| Shell style/model (外壳样式/型号) | ZCG:With two nuts (fixed back and forth)带有两个螺母 (前后固定) |
| Button (按键)                 | A button(一个按键)                                        |
| Termination type (终止类型)     | Female print PCB(印刷PCB)                               |
| Line diameter awg(线材直径)     | 28-20AWG                                              |
| Cable diameterØ (电缆直径)      | 0-0                                                   |
| Match plug(匹配插头)            | TGG.2B.P05.CLAD52H                                    |

| Location pin combination (定位销组合) |                                          |               |                            |
|----------------------------------|------------------------------------------|---------------|----------------------------|
| (编号)<br>Number                   | Number of<br>positioning pins(定<br>位销数量) | Angle(<br>角度) | Series(系列)--2B             |
| G                                | One(1)                                   |               | (Zero degrees)0°           |
| A                                | Two(2)                                   | A             | Thirty degrees(30°)        |
| B                                | Two(2)                                   |               | Forty-five<br>degrees(45°) |
| C                                | Two(2)                                   |               | Sixty degrees(60°)         |
| D                                | Two(2)                                   | γ             | 95 degrees (95°)           |
| E                                | Two(2)                                   | β             | 120 degrees(120°)          |
| F                                | Two(2)                                   |               | 145 degrees(145°)          |
| J                                | Two(2)                                   | A             | 37.5degrees(37.5°)         |
| K                                | Two(2)                                   |               | 52.5degrees(52.5°)         |
| L                                | Two(2)                                   | γ             | Seventy degrees(70°)       |


|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |




|    | A    | N    | L    | E     | M    | S1   | S2   |
|----|------|------|------|-------|------|------|------|
| MM | Ø20  | 21.5 | 24.8 | M15*1 | 3.5  | 13.5 | 17   |
| in | 0.79 | 0.85 | 0.98 |       | 0.14 | 0.53 | 0.67 |




Pcb plate opening size  
(PCB板开孔尺寸)



Pane hole size  
(面板开孔尺寸)



Boarded mother adhesive core  
(板接型母胶芯)



Positive view of the socket  
(插座正视图)

|                                 |     |
|---------------------------------|-----|
| Model(型号)                       | ZC  |
| Positioning pin(定位销)            | G   |
| Series(系列)                      | 2B  |
| Needle core configuration(针芯配置) | P05 |
| Outer casing(外壳)                | C   |
| Insulator(绝缘体)                  | L   |
| Needle core(针芯)                 | N   |

|                                  |          |                                      |          |                                        |
|----------------------------------|----------|--------------------------------------|----------|----------------------------------------|
| DESIGNED(设计)                     | DATE(日期) | SCALE(比例)                            | N/A(不适用) | MODEL TYPE                             |
| CHECKED(校对)                      | DATE(日期) | VIEW(视图)                             | ⊕        | 型号类型: ZCG.2B.P05.CLN                   |
| APPROVED(审核)                     | DATE(日期) | UNIT(单位)                             | MM       | PART NO. 2B5 core socket<br>名称: 2B5芯插座 |
| REVISIONS                        |          | MATERIAL (材料)                        |          | DWG NO.:                               |
| www.helloxkb.com www.helloxkb.cn |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | WEIGHT(重量) SHEET(表) REVISION(修订)       |
|                                  |          |                                      |          | 1/1 A0                                 |